



E5330Bs-2



E5220

interface	USB and Wi-Fi	USB and Wi-Fi
Wi-Fi connection	up to 10 devices	up to 10 devices
USB connection	1 device	1 device
frequency	HSPA+/HSPA/UMTS 2100/900 MHz EDGE/GPRS/GSM 1900/1800/900/850 MHz WLAN : 2400–2483.5 GHz	HSPA+/HSPA/UMTS 2100/900 MHz EDGE/GPRS/GSM 1900/1800/900/850 MHz WLAN : 2400–2483.5 GHz
speed of data exchange	HSPA+` download up to 21.6 Mb/sec, upload up to 5.76 Mb/sec HSDPA` download up to 14.4 Mb/sec, upload up to 5.76 Mb/sec HSUPA` download up to 14.4 Mb/sec, upload up to 5.76 Mb/sec UMTS` download up to 384 Kb/sec, upload up to 384 Kb/sec EDGE` download up to 236.8 Kb/sec, upload up to 236.8 Kb/sec GPRS` download up to 85.6 Kb/sec, upload up to 85.6 Kb/sec WLAN: IEEE 802.11 b/g/n	HSPA+` download up to 21.6 Mb/sec, upload up to 5.76 Mb/sec HSPA` download up to 14.4 Mb/sec, upload up to 5.76 Mb/sec UMTS` download up to 384 Kb/sec, upload up to 384 Kb/sec EDGE` download up to 236.8 Kb/sec, upload up to 236.8 Kb/sec GPRS` download up to 85.6 Kb/sec, upload up to 85.6 Kb/sec WLAN: IEEE 802.11 b/g/n
compatibility with operational	Windows OS	Windows OS

systems	MAC OS	MAC OS
battery life rechargeable Li type	3.7 Watt, 1500mAH maximal working time is 5-6 hours (depending on the network) maximal hibernate time is 300 hours (depending on the network)	3.7 Watt, 1150mAH maximal working time is 4 hours maximal hibernate time is 200 hours when WiFi is turned off, 23 hours when WiFi is turned on
size	14.0mm x 92.8mm x 60.0mm	14.4mm x 90.5mm x 56.0mm
weight	about 74 grams (including the battery)	about 66 grams
temperature	exploitation temperature is 0 C ~ +35 C preserving temperature is -20 C ~ +60 C	exploitation temperature is 0 C ~ +35 C preserving temperature is -20 C ~ +50 C

price	
24 months commitment with 6000 AMD monthly fee	2000 AMD
24 months commitment with 8000, 11 000 or 15 000 AMD monthly fee	1 AMD
12 months commitment with 7000 AMD monthly fee	4000 AMD
12 months commitment with 9000, 12 000, 16 000 AMD monthly fee	1 AMD
Without commitment	39 000 AMD