



E3251



MF 680

interface type	USB 2.0 high speed	USB 2.0 high speed
frequency	WCDMA/HSPA/HSPA+ 850/900/1900/2100 MHz GSM/GPRS/EDGE 850/900/1800/1900 MHz	WCDMA/UMTS 2100/1900/900 MHz EDGE/GPR/GSM 1900/1800/900/850 MHz
transmission (max. data rate)	HSPA+ download 42.2 Mbps HSUPA upload 5.76 Mbps WCDMA download 384 Kbps upload 384 Kbps EDGE download up to 236.8 Kbps GPRS download 85.6 Kbps	DC-HSPA+ download 42.2 Mbps (category 24) HSDPA download 14.4 Mbps (category 10) HSDPA upload 5.76 Mbps (category 6) WCDMA download 384 Kbps, upload 384 Kbps EDGE download 236.8 Kbps
size	80 x 26 x 10.05 mm	78 x 28.2 x 11.7 mm
weight	< 30 g	26.2g
memory	expandable with microSD	expandable with microSD

	(up to 32 GB)	(up to 32 GB)
temperature	storage temperature: -10C ~ +45C operation temperature: -20C ~ +70C	storage temperature: -40C ~ +80C operation temperature: -10C ~ +60C
auto installation	compatible with Windows OS	compatible with Windows OS
compatible operation systems	Windows XP SP3 Windows Vista SP1/SP2 Windows 7, Windows 8 MAC (10.7.10.8), Linux*	Windows 2000 (SP4), Windows XP (SP2 and later), Windows Vista (32 bit), Windows Vista (64 bit) Windows 7, MAC (10.4.10 and later), Linux*

* Please, contact [customer care](#) for supported Linux versions.

price	
With a commitment to stay subscribed during 12 months to U!Flash 8000, 11000 and 15000	1 AMD
U!Flash 42.2 modem can be purchased also without 12 months commitment.	30 000 AMD